



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

HV gate valve, Series 091, DN 80 (ID 3'')
Ordering No. 09138-PE01


Description

Flange	ISO-F 80
Actuator	Manual actuator with detachable handle, self locking in any position, visual position indicator
Number of turns needed for full stroke	33 Turns
Feedthrough	Bellows feedthrough

Technical data

Leak rate	
– Valve body	$< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$
– Valve seat	$< 1 \cdot 10^{-7} \text{ mbar ls}^{-1}$
Pressure range	$1 \cdot 10^{-8} \text{ mbar}$ to 1.2 bar (abs)
Differential pressure on the gate	$\leq 1.2 \text{ bar}$
Conductance (molecular flow)	800 ls^{-1}

Max. differential pressure at opening in closing and opening direction with influence to the cycle life



– Higher pressure on seat side A, the differential pressure acts in opening direction	$\leq 1.0 \text{ bar}$ with full cycle life
– Higher pressure on counter seat side B, the differential pressure acts in closing direction	$\leq 30 \text{ mbar}$ with full cycle life
– Higher pressure on counter seat side B, the differential pressure acts in closing direction	$\leq 1.0 \text{ bar}$ with reduced cycle life
Cycles until first service	5 000 (unheated and under clean conditions)
Bellows cycles	100 000 (unheated and under clean conditions)
Bake-out temperature	
– Valve body	$\leq 150 \text{ }^\circ\text{C}$ (bake-out max. 24h)
– Actuator	$\leq 100 \text{ }^\circ\text{C}$

Created by: MAEM	Release date: 2013-06-20	1 of 2
Modified by:	Release date:	261430EB



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

HV gate valve, Series 091, DN 80 (ID 3'')
Ordering No. 09138-PE01

Heating and cooling rate	50 °C h ⁻¹
Material	
– Valve body	AISI 304 (1.4301)
– Bonnet	EN AW-5083 (3.3547)
– Gate	AISI 304 (1.4301), (1.4308)
– Parts (in contact with media)	A2 Ni-Teflon coated, PEEK
– Bellows	AISI 633, (AM350)
Seal	
– Bonnet	FKM (Viton [®])
– Gate	FKM (Viton [®])
– Actuator	FKM (Viton [®])
Mounting position	any
Weight	approx. 7.8 kg / 17.2 lbs

Created by: MAEM	Release date: 2013-06-20	2 of 2
Modified by:	Release date:	261430EB