

### Product data sheet

# UHV gate valve, Series 108, DN 250 (ID 10") Ordering No. 10848-CE24

### **Description**

Flange CF-F 250

Actuator pneumatic, double acting

with position indicator

Feedthrough Bellows

**Technical data** 

Leak rate – Valve body  $< 5 \cdot 10^{-10}$  mbar ls<sup>-1</sup>

– Valve seat < 1 · 10<sup>-9</sup> mbar Is<sup>-1</sup>

Pressure range  $1 \cdot 10^{-10}$  mbar to 1.2 bar (abs)

Differential pressure on the gate  $\leq$  1.2 bar

Differential pressure at opening  $\leq$  30 mbar

Conductance (molecular flow) 19 990 ls<sup>-1</sup>

Cycles until first service 50 000 (unheated and under clean conditions)

Temperature – Valve Body ≤ 250 °C open / ≤ 200 °C closed (bake-out max. 24h)

(Maximum values: depending — Actuator ≤ 200 °C on operating conditions and — Position indicator ≤ 80 °C

sealing materials)

Heating and cooling rate 50 °C h<sup>-1</sup>

Material (main components) – Valve Body AISI 304 (1.4301)

- Mechanism AISI 316L (1.4404), AISI 304 (1.4301)

- Bellows AISI 316L (1.4404, 1.4435)

Seal – Bonnet metal

– Gate
 – Actuator
 FKM (Viton<sup>®</sup>), O-ring
 FKM (Viton<sup>®</sup>), NBR

Mounting position any

Volume of pneumatic actuator 0.35 I / 0.0122 ft<sup>3</sup>

Compressed air 5-7 bar / 73-102 psi

min. - max. overpressure

Compressed air connection 1/8" ISO / NPT

Created by: SON	Release date: 2013-01-15	1 of 2
Modified by:	Release date:	299143EA



## **Product data sheet**

# UHV gate valve, Series 108, DN 250 (ID 10") Ordering No. 10848-CE24

Actuation time – closing 4 s

- opening 4 s

Weight 52 kg / 115 lbs

Behavior in case of compressed — Valve closed valve remains closed air pressure drop — Valve open undefined


Behavior in case of power failure — Valve closed depending on customer installation

Valve open depending on customer installation

#### **Position indicator**

Type Micro switch
Voltage ≤ 50 V AC / DC

Current max. ≤ 1.2 A



Wiring diagram

Modified by:	Release date:	299143EA
Created by: SON	Release date: 2013-01-15	2 of 2