



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

HV gate valve, Series 110, DN 250 (ID 10'')
Ordering No. 11048-PE01

Description

Flange	ISO-F 250
Actuator	Manual, handwheel
Feedthrough	Bellows

Technical data

Leak rate	- Valve body	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
	- Valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-8}$ mbar to 1.2 bar (abs)
Differential pressure on the gate		≤ 1.2 bar
Differential pressure at opening		≤ 30 mbar
Conductance (molecular flow)		27 110 ls ⁻¹
Cycles until first service		200 000 (unheated and under clean conditions)
Temperature (Maximum values: depending on operating conditions and sealing materials)	- Valve body	≤ 150 °C
	- Actuator	≤ 80 °C
Heating and cooling rate		50 °C h ⁻¹
Material (main components)	- Valve body	AISI 304 (1.4301)
	- Mechanism	AISI 304 (1.4301)
	- Bellows	AISI 633 (AM350)
Seal	- Bonnet	FKM (Viton®)
	- Gate	FKM (Viton®), O-ring
	- Actuator	FKM (Viton®), NBR
Mounting position		any

Created by: MAEM	Release date: 2013-03-27	1 of 1
Modified by:	Release date:	285677EA